



BALANCED PRESSURE THERMOSTATIC STEAM TRAP

MODEL LV13N

Features

Balanced pressure thermostatic trap suitable for small process, tracing, vessels and heaters.

1. "Fail open" feature will not hold back condensate in steam space.
2. Multi-diaphragm construction for long service life.
3. Cyclic operation with fixed subcooling throughout entire pressure range.
4. Outstanding air venting capability.
5. Compact, yet high capacity.
6. Easy to maintain and easy to clean.
7. Hardened stainless steel "flat valve" plus "cone ridge seat" ensure tight shut-off.
8. Built-in screen with large surface area.



Specifications

Model		LV13N
Connection		Screwed
Size (mm)		15, 20
Maximum Operating Pressure (MPaG)	PMO	1.3
Minimum Operating Pressure (MPaG)		0.01
Maximum Back Pressure		90% of Inlet Pressure
Maximum Operating Temperature (°C)	TMO	200
Subcooling of Capsule Fill (°C)		up to 6
Type of X-element		B

PRESSURE SHELL DESIGN CONDITIONS (NOT OPERATING CONDITIONS):
 Maximum Allowable Pressure (MPaG) PMA: 1.6
 Maximum Allowable Temperature (°C) TMA: 220

1 MPa = 10.197 kg/cm²




To avoid abnormal operation, accidents or serious injury,
 DO NOT use this product outside of the specification range.
 Local regulations may restrict the use of this product to
 below the conditions quoted.

No.	Description	Material	JIS	ASTM/AISI*
①	Body	Brass	C3771	B124 C37700
②	Cover	Brass	C3771	B124 C37700
③ ^R	Valve Seat	Stainless Steel	SUS420F	AISI420F
④ ^R	X-element	Stainless Steel	—	—
⑤ ^R	X-element Guide	Stainless Steel	SUS304	AISI304
⑥ ^R	Spring Clip	Stainless Steel	SUS304	AISI304
⑦ ^R	Screen	Stainless Steel	SUS304	AISI304
⑧ ^R	Cover Gasket	Fluorine Resin	PTFE	—
⑨	Nameplate	Stainless Steel	SUS304	AISI304

* Equivalent

Replacement Kits available: (R) repair parts





Dimensions

● **LV13N**
Screwed


LV13N Screwed* (mm)

Size	L	H	H ₁	φD	W ₁	W ₂	Weight (kg)
15	76	65	49	52	32	32	0.55
20	80						

* Rc(PT), other standards available



Discharge Capacity



1. Differential pressure is the difference between the inlet and outlet pressure of the trap.
2. Recommended safety factor: at least 2.

Manufacturer

ISO 9001/ISO 14001

TLV® CO., LTD.
Kakogawa, Japan

is approved by LRQA Ltd. to ISO 9001/14001

